

LED Commercial Downlight - DL2002



Application: Offices, lobbies, conference rooms, schools, retail stores, living rooms, bedrooms, and more residential and commercial applications.

COMPATIBLE ACCESSORIES



Emergency Driver
BLD-HM15D-YYY

DESCRIPTION

A versatile, high-efficiency downlight designed to deliver superior performance, flexible configuration, and modern aesthetics for any lighting application.

- Versatile & Customizable: Available in 4", 6", 8", and 10" sizes to accommodate diverse installation needs, with 5 selectable wattages, 5 CCT options via dip switch, and 3-in-1 dimming—one fixture meets multiple application requirements.
- High Performance & Visual Comfort: Produces 100–120 lm/W with a flicker-free driver, ensuring stable, energy-efficient, and comfortable illumination.
- Durable & Refined Design: Features an integrated lamp body with smooth trim for a clean, elegant look; Type IC rated and Wet Location listed for reliable, long-lasting performance.

SPECIFICATION

Model	HY-CDL04-16W -TWCCT	HY-CDL06-30W -TWCCT	HY-CDL08-35W -TWCCT	HY-CDL10-40W -TWCCT
Power	8W/10W/14W/16W	15W/18W/22W/26W/30W	15W/20W/25W/30W/35W	20W/25W/30W/35W/40W
Size	4"	6"	8"	10"
Input Voltage	AC120-277V			
Dimming	3 in 1 Dimming (0-10V Dimmable @120-277V; Triac Dimmable @120V; ELV Dimmable @120V)			
Lumens	1700 LM @ 16W	3100 LM @30W	4200 LM @35W	4500 LM @40W
Materials	Housing: Aluminum Optics: Polycarbonate (PC)			
Protecting Rating	Wet Location Rated			
Beam Angle	80°		90°	
Power Factor	> 0.9			
CCT	2700K/3000K/3500K/4000K/5000K			
CRI	80			
Working Life	Lumen Maintenance over 70% @50,000+ hours			
Oper. Temperature	-4°F to 104°F (-20°C to 40°C)			
Qty/Package	24PCS/Pack	12PCS/Pack	12PCS/Pack	6PCS/Pack
Package Dim	20.88" × 14" × 19.13"	18.50" × 18.31" × 18.69"	22.81" × 22.63" × 18.69"	25.00" × 12.81" × 20.50"
Package Weight	25 LBS	20 LBS	29 LBS	17 LBS

LED Commercial Downlight - DL2002



Application: Offices, lobbies, conference rooms, schools, retail stores, living rooms, bedrooms, and more residential and commercial applications.

COMPATIBLE ACCESSORIES



Emergency Driver
BLD-HM15D-YYY

DESCRIPTION

A versatile, high-efficiency downlight designed to deliver superior performance, flexible configuration, and modern aesthetics for any lighting application.

- Versatile & Customizable: Available in 4", 6", 8", and 10" sizes to accommodate diverse installation needs, with 5 selectable wattages, 5 CCT options via dip switch, and 3-in-1 dimming—one fixture meets multiple application requirements.
- High Performance & Visual Comfort: Produces 100–120 lm/W with a flicker-free driver, ensuring stable, energy-efficient, and comfortable illumination.
- Durable & Refined Design: Features an integrated lamp body with smooth trim for a clean, elegant look; Type IC rated and Wet Location listed for reliable, long-lasting performance.

SPECIFICATION

Model	HY-CDL04-16W -TWCCT	HY-CDL06-30W -TWCCT	HY-CDL08-35W -TWCCT	HY-CDL10-40W -TWCCT
Power	8W/10W/14W/16W	15W/18W/22W/26W/30W	15W/20W/25W/30W/35W	20W/25W/30W/35W/40W
Size	4"	6"	8"	10"
Input Voltage	AC120-277V			
Dimming	3 in 1 Dimming (0-10V Dimmable @120-277V; Triac Dimmable @120V; ELV Dimmable @120V)			
Lumens	1700 LM @ 16W	3100 LM @30W	4200 LM @35W	4500 LM @40W
Materials	Housing: Aluminum Optics: Polycarbonate (PC)			
Protecting Rating	Wet Location Rated			
Beam Angle	80°		90°	
Power Factor	> 0.9			
CCT	2700K/3000K/3500K/4000K/5000K			
CRI	80			
Working Life	Lumen Maintenance over 70% @50,000+ hours			
Oper. Temperature	-4°F to 104°F (-20°C to 40°C)			
Qty/Package	24PCS/Pack	12PCS/Pack	12PCS/Pack	6PCS/Pack
Package Dim	20.88" × 14" × 19.13"	18.50" × 18.31" × 18.69"	22.81" × 22.63" × 18.69"	25.00" × 12.81" × 20.50"
Package Weight	25 LBS	20 LBS	29 LBS	17 LBS